

MYOPIA EXPERT™ 700

Your Trusted Partner for Myopia Management.



Myopia Expert™ 700, a 2 in 1
accurate and easy to use instrument.



Introduction

2.5 billion people suffer from myopia today.¹

50% of the world's population is predicted to be myopic by 2050.¹

The younger a child becomes myopic the faster their myopia can progress.^{2,3}

Addressing this rising tide requires an accurate and easy to use diagnostic solution.




The Myopia Expert™ 700 is an optical biometer and topographer. It provides a fast and accurate solution* for measuring axial length and corneal topography.

Set yourself apart as a reference in Myopia Care.

Help control axial length growth

Axial Length Measurement

A critical clinical indicator in myopia management.⁴



The earlier myopia progression is controlled, the less likely it is to become more severe.⁵

International Myopia Institute (IMI) recommends a myopia follow-up exam every 6 months.⁶

A 50 µm difference between two follow-up exams indicates some myopia progression.^{7,8}



Myopia Expert™ 700 can measure axial length with an in-vivo repeatability accuracy of +/-27 µm*.

Monitor myopia progression through dedicated chart analysis.

*The Myopia Expert™ 700 has an in-vivo repeatability of +/-27 µm in Axial Length measurement. Visia Imaging (2021). ANNEX 18.7 Statistical Report. Data on file.
1. Holden, B.A., Fricke, T.R., Wilson, D.A., Jong, M., Naidoo, K.S., Sankaridurg, P., Wong, T.Y., Naduvilath, T.J., Resnikoff, S., 2016. Global Prevalence of Myopia and High Myopia and Temporal Trends from 2000 through 2050. *Ophthalmology* 123, 1036-1042.
2. Wolffsohn JS, et al. IMI-myopia control reports overview and introduction. *Investigative ophthalmology & visual science*. 2019;60(3):MI-9.
3. Sankaridurg P. A less myopic future: what are the prospects? *Clin Exp Optom*. 2015;98(6):494-6.

*The Myopia Expert™ 700 has an in-vivo repeatability of +/-27 µm in Axial Length measurement. Visia Imaging (2021). ANNEX 18.7 Statistical Report. Data on file.
4. Jones D, et al. IMI—Instrumentation for Myopia Management. *Investigative Ophthalmology & Visual Science*. 2023 Jul 1;66(9):7-6.
5. Sankaridurg, P., 2015. A less myopic future: what are the prospects? *Clin Exp Optom*, 98 (6), 494-6.
6. Gifford KL, Richdale K, Kang P, Aller TA, Lam CS, Liu YM, Michaud L, Mulder J, Orr JB, Rose KA, Saunders KJ. IMI—clinical management guidelines report. *Investigative ophthalmology & visual science*. 2019 Feb 28;60(3):M184-203.
7. Wolffsohn JS, Kollbaum PS, Berntsen DA, Atchison DA, Benavente A, Bradley A, et al. IMI – Clinical Myopia Control Trials and Instrumentation Report. *Invest Ophthalmol Vis Sci*. 2019;60(3):M132-M60.
8. Moore KE, Berntsen DA. Central and peripheral autorefraction repeatability in normal eyes. *Optom Vis Sci*. 2014;91(9):1106-12.

Become a reference in myopia management

Myopia Expert™ 700 offers a complete set of measurements for a state-of-the-art myopia management service.



Capture multiple measurements for different myopia control solutions with one single instrument.



Easy to use and integrate into your practice

Through its fast* and simple process, Myopia Expert™ 700 provides a smooth and comfortable experience for both the ECP and the patient.



Child friendly by design. Complete acquisitions are done in a few seconds*.



Non-invasive monitoring of axial elongation, without the use of anesthesia, for a comfortable experience for the patient.



Specifications

Measurement specifications

Axial length	Low coherence interferometry		
Corneal topography and keratometry	Keratoscopic cone	24 rings equally distributed on a 43D sphere	
	Analyzed points	Over 100,000	
	Measured points	Over 6,000	
	Corneal coverage	Up to 98 mm on a sphere of radius 8 mm (42.2 diopters with $n = 1.3375$)	
Focus system	Guided focus		
Pupillometry	Infrared LEDs + White LEDs for photopic pupil acquisition		
Fluorescein	Blue LEDs		

Measurement range and accuracy

		Measuring range	Display resolution	In vivo repeatability
Keratometry	Curve radius	5.00 - 12.00 mm	0.01 mm	±0.02 mm
	Curve radius in Diopter (D) ($n=1.3375$)	28.00 - 67.50 D	0.01 D	±0.12 D
Axial length		15.00 - 36.00 mm	0.01 mm	±0.027 mm
Pupil dimension		0.50 - 10.00 mm	0.01 mm	N/A
Limbus (white-to-white)		8.00 - 14.00 mm	0.01 mm	±0.05 mm

Environmental conditions

	In use	Storage	Transport
Temperature	Min 10°C Max 40°C	Min -20°C Max 70°C	Min -20°C Max 70°C
Relative humidity	8 - 75% (non condensing)	8 - 75% (non condensing)	8 - 75% (non condensing)
Atmospheric pressure	800-1060 hPa	700-1060 hPa	700-1060 hPa

Electrical specifications

Power supply	AC 100-240V 50/60 Hz	
Power consumption	100 VA	
Fuse	Type	20 x 5 mm
	Value	T 2.5A H 250 V anti-surge

Mechanical specifications

Width	320 mm / 12.6 in
Height	490 mm / 19.3 in
Length	470 mm / 18.5 in
Weight	18 kg / 40 lbs

PC specifications

Operating system	WINDOWS embedded
Processor	Intel®
RAM	At least 4 GB
Hard disk	At least 500 GB
External connections	LAN integrated, 2x USB



CE 0123
Rx only - For prescription only

Myopia_Expert700-Brochure-WL-US-V1-Jan2026

Myopia Expert 700 is a medical device MDR class IIa.
Legal manufacturer:

Visia Imaging S.r.l. Via Martiri della Libertà, 95/e San Giovanni Valdarno (AR) Italy
For professional use only. Read attentively instructions for use.

© Essilor International - January 2026

